

EZGO **INDUSTRIAL** **875**

The E-Z-GO Industrial 875 offers the versatility needed to handle any tough job plus the unsurpassed reliability E-Z-GO is known for. It features E-Z-GO's durable diamond steel construction, heavy-duty solid state energy control, and is U.L. Certified. It tackles the most demanding jobs around your warehouse or plant facility without question. Leave it to E-Z-GO to produce a vehicle this versatile. What else would you expect from the world's finest utility vehicle maker!





Forward/Reverse Handle & Parking Brake



Cab and Van Box



Convenient Charge Plug Receptacle

INDUSTRIAL 875E

Motor: Heavy Duty 36 volt DC, high efficiency series wound, brazed armature, solid copper windings. 2.5 hp @ 2700 rpm 1 hour.

Electrical System: Six 6-volt heavy duty, deep cycle storage batteries (107 minute, 220 amp-hour @ 20 hr. discharge rate).

Solid State HDI 400 amp rated Controller.

Charger: Powerwise® on board fully automatic with anti-drive away vehicle lockout.

INDUSTRIAL 875G

Engine: 11hp, 4 cycle, 350 cc twin cylinder, overhead cam. Pressurized oil system with washable, permanent filter. Engine mounted air intake with multi-phase silencer and washable filter element.

Transmission: Automatic, continuously variable transmission (CVT) forward and reverse.

Fuel System: 6.5 gallon tank with instrument panel mounted fuel gauge.

SPECIFICATIONS:

Brakes: Hydraulic, drum type, dual rear wheel brakes. Hand parking brake with manual adjustment feature.

Steering: Double reduction rack and pinion.

Speed: Electric - 12-14 mph / Gasoline - 15 mph

Suspension: Heavy duty multiple leaf springs with hydraulic shock absorbers.

DIMENSIONS:

Weight: 875E - 995 lbs., without batteries
875G - 1,036 lbs. dry (fuel capacity 40 lbs.)

Length: 116"

Width: 44.5"

Height: 45" (at steering wheel)

Cargo Deck: 44.5" wide, 69" long

Ground Clearance: 5" (at differential)

Wheel Base: 56"

Turning Clearance Diameter: 20'11"

Intersecting Aisle Clearance: 84"

Tires: 5.7 x 8 (6 ply rated) USA Trail, Load Range C

Load Capacity: 875E - 3,000 lbs.

875G - 1,600 lbs.

(including operator, passenger, accessories and cargo)

FEATURES:

Cargo Deck: Plywood hinged for access to drive package and storage area.

Chassis: Welded high yield strength tubular steel. DuraShield™ Powder Paint coated.

Body: Heavy duty four-way diamond pattern body panels. DuraShield™ Powder Paint coated.

Operation: Removable switch key, reverse warning indicator, floor mounted horn button.

Lights: Dual Halogen headlights, taillights, and brake lights.

Internal Storage: 44.25" W x 12" L x 14" H (Located under hinged plywood deck).

OPTIONS AND ACCESSORIES:

Cab With Windshield Wiper (with or without doors)

Canopy (White or Champagne)

Drop Down Steel Side Rails

Drop Side Metal Bed with Tool Box

Forward Motion Indicator

Front Bumper

Galvanized Steel Over Plywood Cargo Deck

Heavy Duty 12V Battery

Hour Meter

Hydraulic Front Brakes

Muffler Spark Arrester Kit

Non-Standard Paint Color

Plastic Tool Box

Roll Out Battery

Rear Hitch (Pintle or "E")

Stake Side Bodies (Wood)

State of Charge Meter (LED)

U.L. Approved "EE" Classification

Van Box (Steel 69"L x 44"H x 46" W)

Weather Protection Package

Windshield

Specifications subject to change without notice.



E-Z-GO vehicles meet the most stringent manufacturing and safety standards in the industry. All of our electric vehicles have been thoroughly inspected to meet the criteria necessary for the U.L. Label of Certification. Both the gas and electric vehicles meet all of the applicable safety standards, including: ASME's/ANSI B56.8, ANSI/NFPA-505, ANSI/UL-583, and OSHA 1910.178 for industrial trucks.

EZGO INDUSTRIAL 875


THE FINEST UTILITY VEHICLES
IN THE WORLD.™

P.O. Box 388, 1451 MARVIN GRIFFIN ROAD
AUGUSTA, GA 30903-0388 USA
(706) 798-4311 • Fax (706) 796-4540 • (800) 241-5855
WWW.EZGO.COM • E-MAIL: EZGO@EZGO.TEXTRON.COM
© 1998 E-Z-GO DIVISION OF TEXTRON INC.
82096-G1